



Breathable Air Systems



Due to the increasing demand for improved environmental and safety control, Walker Filtration have compiled a comprehensive range of wall mounted and portable breathable air products.

Carefully research and tested to ensure high levels of performance and integrity, these breathable air filter products can be installed where safe breathable compressed air is required.

The filter packages offer filtration and oil removal efficiencies down to 0.01 micron particulate size and maximum oil carryover efficiencies to 0.003 mg/m³ (0.003 ppm) offering the operator clean, particulate and liquid oil free air with the added benefit of taste and odour removal for improved user comfort and performance, exceeding the requirements of AS/NZS1715.

These modular systems provide flexibility and reliability across a wide variety of applications such as:

- » [Diving](#)
- » [Shot Blasting](#)
- » [Spray Painting](#)
- » [Metal Spraying](#)
- » [Welding](#)

Designed and manufactured to exacting standards, these units are widely available across Australia and New Zealand.

The ultimate filtration & drying technology



Technical Specification

Multistage filtration packages specially designed for Breathing Air applications. Included pressure regulator and outlet manifold. Systems are available as wall mounted or frame mounted systems.

Model Number	Pipe Size	Flow Rate SCFM @ 7 barg	Description	Up to Number of Persons see note 1
RSB3-25-2	1/4"	25	0.01 micron coalescing and activated carbon filtration, Distribution Manifold, Regulator and mounting bracket	3
RSB3-35-2	3/8"	35		5
RSB3-50-2	1/2"	50		7
RSB3-25-3	1/4"	25	1 micron prefilter, 0.01 micron coalescing and activated carbon filtration, Distribution Manifold, Regulator and mounting bracket	3
RSB3-35-3	3/8"	35		5
RSB3-50-3	1/2"	50		7
RSB3-25-4	1/4"	25	Water Separator, 1 micron prefilter, 0.01 micron coalescing and activated carbon filtration, Distribution Manifold, Regulator and mounting bracket	3
RSB3-35-4	3/8"	35		5
RSB3-50-4	1/2"	50		7



technical notes

- Based on Breathing Air Standard AS/NZS1715 requirements of 170 l/min per man.
- These systems do not remove toxic gases such as CO and CO₂. Please contact Walker Filtration if you require toxic gas removal.
- For application with higher flow rate, please contact Walker Filtration.

specification

Particle removal	0.01 micron
Max. oil carryover @ 20°C	0.003 mg/m ³ (0.003 ppm)
Max recommended temperature	25°C
Element change X1/XA	12 months
Element change AC	1000 hours / 6 months
Max. working pressure	10 barg

The above systems are wall mounted versions. For frame mounted add '-F' to part number e.g. RSB3-25-3-F
For outlet quick connect couplings add number of couplings followed by 'C' e.g. RSB3-25-3-F-2C



WALKER
FILTRATION



1/8 Isa Way, Boronia Victoria 3155
PO Box 109 Kilsyth Victoria 3137
Ph: (03) 9728 5250
Fax: (03) 9752 0855
Email: info@ccasystems.com.au
Web: www.respiratorysolutionsaustralia.com.au

